

**Pneumatic control valve in two way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)**
**Spindle sealing with PTFE-V-ring unit**

DN 15-100, 1-5kN- actuator, standard Kvs-values.....	321 4/5...
DN 15-50, 1-5kN- actuator, reduced Kvs-values.....	321 4/5...red1
DN 65-100, 1-5kN- actuator, reduced Kvs-values.....	321 4/5...red2
DN 50-100, 10kN- actuator.....	321 4/5...Se
DN 80-150, 14/20kN- actuator.....	321 4/5...Sg/i
DN 200, 14/24kN- actuator.....	321 4/520Sg/k

**Pneumatic control valve in two way form, PN 40, GP240GH+N (GS-C25N)**
**Spindle sealing with PTFE-V-ring unit**

DN 15-100, 1-5kN- actuator, standard Kvs-values.....	321 7...
DN 15-50, 1-5kN- actuator, reduced Kvs-values.....	321 7...red1
DN 65-100, 1-5kN- actuator, reduced Kvs-values.....	321 7...red2
DN 50-100, 10kN- actuator.....	321 7...Se
DN 65-100, 14/20kN- actuator.....	321 7...Sg/i

**Pneumatic control valve in three way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)**
**Spindle sealing with PTFE-V-ring unit**

DN 15-150, 1-5kN- actuator, with mixing plug.....	331 4/5...
DN 50-150, 14kN- actuator, with mixing plug.....	331 4/5...Sg
DN 200, 14kN- actuator, with mixing plug.....	331 4/520Sg
DN 32-150, 1-5kN- actuator, with diverting plug.....	332 4/5...
DN 50-150, 14kN- actuator, with diverting plug.....	332 4/5...Sg
DN 200, 12-18kN- actuator, with diverting plug.....	332 4/520Sf/g/h

**Pneumatic control valve in two way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)**
**Spindle sealing with bellow**

DN 15-150, 1-5kN- actuator.....	351 4/5...
DN 50-100, 10-14kN- actuator.....	351 4/5... Se/g
DN 125-150, 14-20kN- actuator.....	351 4/5... Sg/h/i

**Pneumatic control valve in two way form, PN 40/25, GP240GH+N (GS-C25N)**
**Spindle sealing with bellow PN25**

DN 15-100, 1-5kN- actuator.....	351 6...
DN 50-100, 10-14kN- actuator.....	351 6... Se/g

**Pneumatic control valve in three way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)**
**Spindle sealing with bellow**

DN 15-150, 1-5kN- actuator, with mixing plug.....	361 4/5...
DN 15-100, 1-5kN- actuator, with mixing plug, with weld-on ends.....	361 4/5...fs
DN 32-150, 1-5kN- actuator, with diverting plug.....	362 4/5...

**Pneumatic control valve PN16, bronze CC491K (Rg5).....** 381...  
**in three or two way form with thread connectors**

**Accessories:** see page 2

**Operating instructions:** see group 0

**Accessories:**

Pneumatic (P/P) positioner.....	3905...
Electropneumatic (I/P) positioner.....	3908...
Solenoid valve for operating air.....	393...
Pneumatic accessories.....	394...
Accessories for pneumatic actuator 3f1.....	39e...
Additional limit switch	

**Pneumatic actuators:**

Pneumatic actuator type 3f1.....	3f1...
Thrust 1-5 kN, diaphragm area 250 cm <sup>2</sup>	