

Motor control valve in two way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)
Spindle sealing with PTFE-V-ring unit

DN 15-100, 2-5,5kN- actuator, standard Kvs-values.....	421 4/5...
DN 15-50, 2-5,5kN- actuator, reduced Kvs-values.....	421 4/5...red1
DN 65-100, 2-5,5kN- actuator, reduced Kvs-values.....	421 4/5...red2
DN 50-150, 8-15kN- actuator.....	421 4/5...He/f/h
DN 80-150, 15-25kN- actuator.....	421 4/5...Hh/i/k
DN 200, 12-25kN- actuator.....	421 4/520Hf/h/i/k

Motor control valve in two way form, PN 40, GP240GH+N (GS-C25N)
Spindle sealing with PTFE-V-ring unit

DN 15-100, 2-5,5kN- actuator, standard Kvs-values.....	421 7...
DN 15-50, 2-5,5kN- actuator, reduced Kvs-values.....	421 7...red1
DN 65-100, 2-5,5kN- actuator, reduced Kvs-values.....	421 7...red2
DN 50-100, 8-12kN- actuator.....	421 7...He/f
DN 65-100, 12-25kN- actuator.....	421 7...Hh/i/k

Motor control valve in three way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)
Spindle sealing with PTFE-V-ring unit

DN 15-150, 2-5,5kN- actuator, with mixing plug.....	431 4/5...
DN 50-150, 8-15kN- actuator, with mixing plug.....	431 4/5...He/f/h
DN 200, 12-15kN- actuator, with mixing plug.....	431 4/520Hf/h
DN 32-150, 2-5,5kN- actuator, with diverting plug.....	432 4/5...
DN 50-150, 8-15kN- actuator, with diverting plug.....	432 4/5...He/f/h
DN 200, 12-25kN- actuator, with diverting plug.....	432 4/520Hf/h/i/k

Motor control valve in two way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)
Spindle sealing with bellow

DN 15-150, 2-5,5kN- actuator.....	451 4/5...
DN 50-150, 8-15kN- actuator.....	451 4/5...He/f/h

Motor control valve in two way form, PN 40/25, GP240GH+N (GS-C25N)
Spindle sealing with bellow PN25

DN 15-100, 2-5,5kN- actuator.....	451 6...
DN 50-100, 8-15kN- actuator.....	451 6...He/f/h

Motor control valve in three way form, PN 16/25, EN-GJS-400-18-LT (GGG-40.3)
Spindle sealing with bellow

DN 15-150, 2-5,5kN- actuator, with mixing plug.....	461 4/5...
DN 15-100, 2-5,5kN- actuator, with mixing plug, with weld-on ends.....	461 4/5...fs
DN 32-150, 2-5,5kN- actuator, with diverting plug.....	462 4/5...

Motor control valve PN16, bronze CC491K (Rg5)..... 481...
in three or two way form with thread connectors

Accessories: see page 2

Operating instructions: see group 0

Accessories:

Additional load dependent limit switch.....	49e.
Potentiometer.....	49f...
Process controller integrated into actuator.....	49r...
Digital positioner integrated into actuator.....	49sr5...
Additional travel dependent signal switch.....	49w.

Electrical actuators:

Electrical actuators type 4e1.....	4e1...
Thrust 1,5-5,5 kN	
Electrical, explosion proof actuators type 4ex.....	4ex...
PTB-certified in accordance to ATEX directive 94/9/EC for zone 1, 2, 21, 22, Thrust 0,5-10 kN alternatively suitable for most KFM-control valve types	

Other types of actuators, for instance AUMA or SCHIEBEL products, are alternatively suitable for most KFM-control valve types (on request)